



# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

### Section: 1. Product and Company Identification

#### 1.1 Product Identifier

Product form	Substance
Product Name	Carbon dioxide
CAS No	124-38-9
Formula	100% CO <sub>2</sub>
Other means of identification	Zenith Sparkling Gas, CARBON DIOXIDE, CO <sub>2</sub>

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substances/mixture	Beverage product dispensing. Use as directed.
-------------------------------	---

#### 1.3 Details of supplier of the safety data sheet

	Zenith Heaters Ltd Unit 2/15 Moselle Avenue Henderson Auckland 0610 Telephone 0800 558 055 Email <a href="mailto:sales@zenithheaters.co.nz">sales@zenithheaters.co.nz</a> <a href="http://www.zenithwater.co.nz">www.zenithwater.co.nz</a>
--	--

#### 1.4 Emergency telephone number

Emergency telephone number	0800 558 055
----------------------------	--------------

### Section: 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

<b>Hazard Class and Category Code Regulation EC 1272/2008 (CLP)</b>	
Physical hazards	Gases under pressure – Liquefied gas – Warning – (CLP: Press. Gas) - H280/H281
<b>Classification EC 67/548 or EC 1999/45</b>	
	Not classified as dangerous substance/mixture.

#### 2.2 Label elements

##### Labelling Regulation EC 1272/2008 (CLP)

Hazard Pictogram	
Hazard pictogram code	GHS04
Signal word	Warning
Hazard statement	H281 - Contains refrigerated gas; may cause cryogenic burns or injury H280 - Contains gas under pressure; may explode if heated
Precautionary statements	
Prevention	P202 - Do not handle until all safety precautions have been read and understood P261 - Avoid breathing gas



# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

	P262 - Do not get in eyes, on skin, or on clothing
<b>Response</b>	P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice / attention.
<b>Storage</b>	P403 - Use and store in a well-ventilated place Keep container below 50°C

### 2.3 Other Hazards

#### Other hazards not contributing to the classification

Asphyxiant in high concentrations  
Contact with liquid may cause cold burns/frostbite

### 2.4 Unknown acute toxicity

No data available

## Section: 3. Composition/Information on ingredients

### 3.1 Substance

Name		Carbon dioxide			
Name	Content	CAS No	EC No	Annex No	Classification
Carbon Dioxide	100%	124-38-9	204-696-9	----- *1	Not classified (DSD/DPD) Liq. Gas (H280/H281)
		Contains no other components or impurities which will influence the classification of the product. * 1: Listed in Annex IV / V REACH, exempted from registration. * 2: Registration deadline not expired. * 3: Registration not required: Substance manufactured or imported < 1t/y Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16			

### 3.2 Mixture

N/A

## Section: 4. First aid measures

### 4.1 Description of first aid measures

<b>Inhalation</b>	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.  Low concentrations of CO <sub>2</sub> cause increased respiration and headache.  Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
<b>Eye contact</b>	Immediately flush eyes thoroughly with water for at least 15 minutes.  In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
<b>Skin contact</b>	MAY CAUSE FROSTBITE. For exposure to liquid, cold vapour, or solid carbon dioxide (dry ice), immediately warm frostbite area with warm water not to exceed 41°C. Water temperature should be tolerable to normal skin. Maintain skin warming for at least 15 minutes or until normal colouring and sensations have returned to the affected area. In case of massive exposure, remove clothing while showering with warm water. Seek medical evaluation and treatment as soon as possible.



# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

Ingestion	Ingestion is not considered a potential route of exposure
<b>4.2 Most important symptoms and effects, both acute and delayed</b>	
	No additional information available
<b>4.3 Indication of any immediate attention and special treatment needed</b>	
	None
<b>Section: 5. Firefighting measures</b>	
<b>5.1 Extinguisher media</b>	
Suitable extinguishing media	Use extinguishing media appropriate for surrounding fire.
<b>5.2 Special hazard arising from the substance or mixture</b>	
Explosion hazard	Heat of fire can build pressure in container and cause it to rupture. Containers are equipped with a pressure relief device. No part of the container should be subjected to a temperature higher than 50°C.
Reactivity	No reactivity hazard other than the effects described in sub-sections below.
<b>5.1 Advice for firefighters</b>	
Specific methods	If possible, stop flow of product. Coordinate fire measure to the surrounding fire. Cool endangered containers with water spray jet from a protected position. Do not empty contaminated fire water into drains. Move away from the container and cool with water from a protected position. If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire.
Special protective equipment for firefighters	In confined space use self-contained breathing apparatus.
Flammable class	Non-flammable.
<b>Section: 6. Accidental release measures</b>	
<b>6.1 Personal precautions, protective equipment and emergency procedures</b>	
Personal precautions	WARNING! Liquid and gas under pressure. Rapid release of gaseous carbon dioxide through a valve can result in the formation of dry ice, which is very cold and can cause frostbite. Evacuate area. Use protective clothing. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation.
<b>6.2 Environmental precautions</b>	
	Try to stop release. Prevent from entering sewers, basements and work pits, or any place where its accumulation can be dangerous.
<b>6.3 Methods and material for containment and cleaning up</b>	
Clean up methods	Ventilate area. Prevent waste from contaminating the surrounding environment. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If



# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

necessary, call your local supplier for assistance.

### 6.4 Reference to other sections

See also sections 8 and 13.

## Section: 7. Handling and Storage

### 7.1 Precautions for safe handling

#### Safe use of product

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.  
Only experienced and properly instructed persons should handle gases under pressure.  
The product must be handled in accordance with good industrial hygiene and safety procedures.  
Do not smoke while handling product.  
Ensure the complete gas system was (or is regularly) checked for leaks before use.

#### Safe handling of gas receptacle

Refer to supplier's container handling instructions.  
Do not allow back feed into the container.  
Protect cylinders from physical damage; do not drag, roll, slide or drop.  
When moving bulk cylinders/containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport bulk cylinders/containers.  
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.  
If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.  
Never attempt to repair or modify container valves or safety relief devices.  
Damaged valves should be reported immediately to the supplier.  
Keep container valve outlets clean and free from contaminants particularly oil and water.  
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.  
Close container valve after each use and when empty, even if still connected to equipment.  
Never attempt to transfer gases from one cylinder/container to another.  
Never use direct flame or electrical heating devices to raise the pressure of a container.  
Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

#### General

Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Potential production of solid CO<sub>2</sub> particles must be ruled out. In order to rule out potential electrostatic discharge production, the system must be adequately grounded.

#### Handling

Suck back of water into the container must be prevented.  
Do not allow backfeed into the container.  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.



# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

Refer to supplier's container handling instructions.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep away from combustible materials.  
Keep container below 50°C in a well ventilated place.  
Observe all regulations and local requirements regarding storage of containers.  
Containers should not be stored in conditions likely to encourage corrosion.  
Containers should be stored in the vertical position and properly secured to prevent toppling.  
Stored containers should be periodically checked for general condition and leakage.  
Container valve guards or caps should be in place.  
Store containers in location free from fire risk and away from sources of heat and ignition.

#### Storage

Keep container below 50°C in a well ventilated place.

### 7.3 Specific end use

None

## Section: 8. Exposure control/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits Carbon dioxide

- x Value 8h (CZ) [mg/m<sup>3</sup>] : 9000
- x ILV (EU) - 8 H - [mg/m<sup>3</sup>] : 9000
- x ILV (EU) - 8 H - [ppm] : 5000
- x TLV<sup>©</sup> -TWA [ppm] : 5000
- x TLV<sup>©</sup> -STEL [ppm] : 30000
- x AGW (8h) - Germany [mg/m<sup>3</sup>] TRGS 900 : 9100
- x AGW (8h) - Germany [ppm] TRGS 900 : 5000
- x MAK (AU) Tagesmittelwert (ml/m<sup>3</sup>) : 5000
- x MAK (AU) Tagesmittelwert (mg/m<sup>3</sup>) : 9000
- x MAK (AU) Kurzzeitwerte (ml/m<sup>3</sup>) : 10000
- x MAK (AU) Kurzzeitwerte (mg/m<sup>3</sup>) : 18000
- x VLA-ED - Spain [ppm] : 5000
- x VLA-ED - Spain [mg/m<sup>3</sup>] : 9150
- x VLA-EC - Spain [ppm] : 15000
- x VLA-EC - Spain [mg/m<sup>3</sup>] : 27400
- x NGV - [ppm] : 5000
- x NGV - [mg/m<sup>3</sup>] : 9000
- x KTV - [ppm] : 10
- x KTV - [mg/m<sup>3</sup>] : 10
- x HTP-värden (FI) - 8 H - [ppm] : 5000
- x HTP-värden (FI) - 8 H - [mg/m<sup>3</sup>] : 9100
- x Grænserværdier (DK) (ppm) : 5000
- x Grænserværdier (DK) (ppm) : 9000
- x Grænserværdier (DK) : 9000
- x GV Value Limit (Norway) [ppm] : 5000
- x GV Value Limit (Norway) [mg/m<sup>3</sup>] : 9000
- x 8-Hour TWA (PL) (NDS) (mg/m<sup>3</sup>) : 9000
- x 15-Minute STEL (PL)(NDSch) (mg/m<sup>3</sup>) : 27000
- x Valori Limite di Soglia (IT) 8 ore [ppm] : 5000
- x Valori Limite di Soglia (IT) 8 ore [mg/m<sup>3</sup>] : 9000



# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

- x TLV-TWA (Belgium) (ppm) : 5000
  - x TLV-STEL (Belgium) (ppm) : 30000
  - x Value 15min. (CZ) [mg/m<sup>3</sup>] : 45000
- In Australia, the recognised exposure limits for CO<sub>2</sub> reference an 8-hour Time Weighted Average (TWA) of 5,000 ppm and a 15 minute Short Term Exposure Limit (STEL) of 30,000 ppm. CO<sub>2</sub> at 40,000 ppm is considered Immediately Dangerous to Life or Health (IDLH).*

**DNEL: Derived no effect level**

None available

**PNEC: Predicted no effect concentration**

None available

### 8.2 Exposure control

#### 8.2.1 Appropriate engineering control

Systems under pressure should be regularly checked for leakages.  
Provide adequate general and local exhaust ventilation.  
Consider work permit system e.g. for maintenance activities.

#### 8.2.2 Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.  
The following recommendations should be considered.  
Wear safety glasses with side shields  
Wear leather safety gloves and safety shoes when handling cylinders.

#### Personal protection

Ensure adequate ventilation.  
Protect eyes, face and skin from liquid splashes.

#### 8.2.3 Appropriate engineering control

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

## Section: 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Appearance - Physical state at 20°C / 101.3kPa**

Liquefied gas

**Colour**

Colourless.

**Odour**

No odour warning properties.

**Odour threshold**

Odour threshold is subjective and inadequate to warn for overexposure.

**pH value**

Not applicable for gas-mixtures

**Molar mass [g/mol]**

Not applicable for gases and gas-mixtures.

**Melting point [°C]**

-56.6

**Boiling point [°C]**

-78.5 (s)

**Critical temperature [°C]**

30

**Flash point [°C]**

Not applicable for gas-mixtures.

**Evaporation rate (ether=1)**

Not applicable for gas-mixtures.

**Flammability range [vol% in air]**

Non-flammable

**Vapour pressure [20°C]**

57.3 bar  
Not applicable



# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

Relative density, gas (air=1)	1.52
Relative density, liquid (water=1)	1.03
Solubility in water [mg/l]	2000
Partition coefficient n-octanol/water	Not applicable for gas-mixtures.
Viscosity at 20°C [mPa.s]	Not applicable.
Explosive Properties	Not applicable.

### 9.2 Other information

Gas group	Liquefied gas
Additional information	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
Molecular weight	44

## Section: 10. Stability and reactivity

### 10.1 Reactivity

Stability and reactivity	No reactivity hazard other than the effects described in sub-sections below. Stable under normal conditions. Liquid spillages can cause embrittlement of structural materials.
--------------------------	--

### 10.2 Chemical stability

	Stable under normal conditions
--	--------------------------------

### 10.3 Possibility of hazardous reactions

	None
--	------

### 10.4 Conditions to avoid

	None
--	------

### 10.5 Incompatible materials

	None
--	------

### 10.6 Hazardous decomposition products

	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
--	--

## Section: 11. Toxicological information

### 11.1 Information on toxicological effects

Toxicity information	In high concentrations cause rapid circulatory insufficiency even at normal levels of oxygen concentration. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness and death
Acute toxicity	No known toxicological effects from this product.
Rat inhalation LC50 [ppm/4h]	No data available.
Skin corrosion/irritation	No known effects from this product.
Serious eye damage/irritation	No known effects from this product.
Respiratory or skin sensitisation	No known effects from this product.
STOT-single exposure	No known effects from this product.
STOT-repeated exposure	No known effects from this product.



# Carbon Dioxide


## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

Aspiration hazard	Not applicable for gases and gas-mixtures
<b>Section: 12. Ecological information</b>	
<b>12.1 Toxicity</b>	
	No data available
<b>12.2 Persistence – degradability</b>	
	No data available
<b>12.3 Bioaccumulative potential</b>	
	No data available
<b>12.4 Mobility in soil</b>	
	No data available
<b>12.5 Results of PBT and vPvB assessment</b>	
	No data available
<b>12.6 Other adverse effects</b>	
Ecological effects information	When discharged in large quantities may contribute to the greenhouse effect. Can cause frost damage to vegetation.
Effect on global warming	Contains greenhouse gas(es) not covered by 842/2006/EC
Global warming potential [CO <sub>2</sub> =1]	1
<b>Section: 13. Disposal consideration</b>	
<b>13.1 Waste treatment methods</b>	
	May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous. Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at <a href="http://www.eiga.org">http://www.eiga.org</a> ) for more guidance on suitable disposal methods. Contact supplier if guidance is required.
General	Do not discharge into any place where its accumulation could be dangerous. Discharge to atmosphere in large quantities should be avoided. Contact supplier if guidance is required.
<b>13.2 Additional information</b>	
	None
<b>Section: 14. Transport information</b>	
UN Number	1013
Labelling ADR, IMDG, IATA	 2.2: Non-flammable, non-toxic gas
Land transport (ADR/RID)	
H.I. nr	20





# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

UN proper shipping name	CARBON DIOXIDE
Transport hazard class(es)	2
Classification code	2 A
Packing Instruction(s)	P200
Tunnel Restriction	C/E Tank carriage: Passage forbidden through tunnels of category C, D and E; Other carriage: Passage forbidden through tunnels of category E
HAZCHEM - Emergency Action Code	2T 2 = Fine water spray. T = Recommended personal protective equipment: Full fire kit and breathing apparatus. Appropriate measures: dilute.
<b>Sea transport (IMDG)</b>	
Proper shipping name	CARBON DIOXIDE
Class	2.2
Emergency Schedule (EmS) - Fire	F-C
Emergency Schedule (EmS) - Spillage	S-V
Packing instruction	P200
<b>Air transport (ICAO-TI/IATA-DGR)</b>	
Proper shipping name (IATA)	CARBON DIOXIDE
Class	2.2
Passenger and Cargo Aircraft	Allowed.
Packing instruction - Passenger and Cargo Aircraft	200
Packing instruction - Cargo Aircraft only	200
<b>Special precaution for user</b>	
	<ul style="list-style-type: none"><li>x Avoid transport on vehicles where the load space is not separated from the driver's compartment.</li><li>x Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.</li><li>x Before transporting product containers :<ul style="list-style-type: none"><li>o Ensure there is adequate ventilation.</li><li>o Ensure that containers are firmly secured.</li><li>o Ensure cylinder valve is closed and not leaking.</li><li>o Ensure valve outlet cap nut or plug (where provided) is correctly fitted.</li><li>o Ensure valve protection device (where provided) is correctly fitted.</li></ul></li></ul>
Labelling ADR	2.2: Non-flammable, non-toxic gas.
In case of spillage and/or leakage	Clean up even minor leaks or spills if possible without unnecessary risk



# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

<b>Other transport information</b>	<ul style="list-style-type: none"><li>x Avoid transport on vehicles where the load space is not separated from the driver's compartment.</li><li>x Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.</li><li>x Before transporting product containers :<ul style="list-style-type: none"><li>o Ensure that containers are firmly secured.</li><li>o Ensure there is adequate ventilation.</li><li>o Compliance with applicable regulations.</li></ul></li></ul>
<b>Personal precautions</b>	The driver shall not attempt to deal with any fire of the load.
<b>Emergency action in case of accident</b>	Stop the engine. No naked lights. No smoking. Mark roads and warns other road users. Keep public away from danger area. NOTIFY POLICE AND FIRE BRIGADE IMMEDIATELY.
<b>Additional information</b>	None
<b>Section: 15. Regulatory information</b>	
<b>15.1 Safety, health and environmental regulations/legislation specific for substance or mixture</b>	
<b>EU legislation</b>	
<b>Seveso directive 96/82/EC</b>	Not covered.
<b>National legislation</b>	
	Ensure all national/local regulations are observed
<b>15.2 Chemical Safety Assessment</b>	
	A CSA does not need to be carried out for this product
<b>Section: 16. Other information</b>	
<b>Indication of changes</b>	Revised safety data sheet in accordance with commission regulation (EU) No 453/2010
<b>Training advice</b>	Asphyxiant in high concentrations. Receptacle under pressure. May cause frostbite. Keep container in a well-ventilated place. Do not breathe the gas. Ensure all national/local regulations are observed. The hazard of asphyxiation is often overlooked and must be stressed during operator training.
<b>List of full text of H-statements in section 3</b>	H280 - Contains gas under pressure; may explode if heated.
<b>Further information</b>	Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP / (EC) 1999/45 DPD. This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
<b>Note</b>	This Safety Data Sheet has been established in accordance with the applicable European Union legislation.



# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

**Date of issue: 07/12/2016**

**Revision edition no.: 3**

**Supersedes: 30/05/2012**

### DISCLAIMER OF LIABILITY

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

The contents and format of this SDS are in accordance with EC Commission Directive 2001/58/EC.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

**End of document.**



# Carbon Dioxide

## Safety Data Sheet PN-800758NZ

This SDS conforms to Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals

Date of issue: 07/12/2016

Revision edition no.: 3

Supersedes: 30/05/2012

**Left Blank Intentionally**