

## ZIP HYDROTAP G4 4IN1 BCHA 240/175 CLASSIC MIXER

## Order Code HT1724D

Zip HydroTap 4 in 1 Boiling, Chilled, Filtered drinking water plus Hot and Cold washing up water from two seperate taps. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.

| Manufacturing<br>Code    | 5361AU0H0CN1C |
|--------------------------|---------------|
| Capacity                 | Commercial    |
| Disability Options       | yes           |
| Boiling Cups per<br>hour | 240           |
| Chilled Cups per<br>hour | 175           |



| Тар                          | Zip HydroTap CLASSIC Tap (Chrome)  |  |  |  |  |
|------------------------------|--|--|--|--|--|
| Water Pressure               | Min 250kPa - Max 700kPa  |  |  |  |  |
| Water Connection             | 12.7mm BSP   |  |  |  |  |
| Water Supply<br>Requirements | Cold   |  |  |  |  |
| Water Valves                 | Integrated 500kPa Pressure limiting valve and Dual Check Valve                 |  |  |  |  |
| Power Rating                 | 2.2kW 220-240V 50/ 60Hz  |  |  |  |  |
| Booster Power Rating         | Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz                                   |  |  |  |  |
| Power Supply                 | 2 x 10Amp GPO's (or 1 x 10Amp Double GPO)                                      |  |  |  |  |
| Dimensions                   | H333mm x W394mm x D464mm   |  |  |  |  |
| Product Approvals            | WaterMark, CE, RCM, ARC  |  |  |  |  |
| Wels Rating                  | 6 Star, 3.0 litres   |  |  |  |  |
| Warranty                     | 5 years (appliance warranty 36 months plus additional 24 months tank warranty) |  |  |  |  |
|                              |  |  |  |  |  |

## Installation Requirements

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

## Installation Detail

