

ZIP HYDROTAP G4 BCS 160/175

Order Code HT1762Z3

Zip HydroTap Boiling, Chilled, Sparkling, Filtered water appliance featuring a single under bench command centre including full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 3 energy saving modes including sensor activated "sleep when its dark", 0.2 micron water filtration and a refillable CO2 cylinder.

Manufacturing Code	5053AU0S0ZN1C
Capacity	Commercial
Disability Options	Unavailable
Boiling Cups per hour	160
Combined Chilled and Sparkling Cups per hour	175



TapZip HydroTap CLASSIC Tap (Matte Black)Water PressureMin 250kPa - Max 700kPaWater Connection12.7mm BSPWater Supply RequirementsColdWater ValvesIntegrated 500kPa Pressure limiting valve and Dual Check ValvePower Rating2.3kW 220-240V 50/ 60HzPower Supply1 x 10Amp GPODimensionsH333mm x W394mm x D464mmProduct ApprovalsWaterMark, CE, RCM, ARCWarranty5 years (appliance warranty 36 months plus additional 24 months tank warranty)						
Water Connection 12.7mm BSP Cold Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 2.3kW 220-240V 50/ 60Hz Power Supply 1 x 10Amp GPO Dimensions H333mm x W394mm x D464mm Product Approvals WaterMark, CE, RCM, ARC	Тар	Zip HydroTap CLASSIC Tap (Matte Black)				
Water Supply Cold Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 2.3kW 220-240V 50/ 60Hz Power Supply 1 x 10Amp GP0 Dimensions H333mm x W394mm x D464mm Product Approvals WaterMark, CE, RCM, ARC	Water Pressure	Min 250kPa - Max 700kPa				
Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 2.3kW 220-240V 50/ 60Hz Power Supply 1 x 10Amp GPO Dimensions H333mm x W394mm x D464mm Product Approvals WaterMark, CE, RCM, ARC	Water Connection	12.7mm BSP				
Power Rating 2.3kW 220-240V 50/ 60Hz Power Supply 1 x 10Amp GP0 Dimensions H333mm x W394mm x D464mm Product Approvals WaterMark, CE, RCM, ARC		Cold				
Power Supply 1 x 10Amp GP0 Dimensions H333mm x W394mm x D464mm Product Approvals WaterMark, CE, RCM, ARC	Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve				
Dimensions H333mm x W394mm x D464mm Product Approvals WaterMark, CE, RCM, ARC	Power Rating	2.3kW 220-240V 50/ 60Hz				
Product Approvals WaterMark, CE, RCM, ARC	Power Supply	1 x 10Amp GP0				
	Dimensions	H333mm x W394mm x D464mm				
Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)	Product Approvals	WaterMark, CE, RCM, ARC				
	Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)				

Installation Requirements

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

Installation Detail

