

## ZIP HYDROTAP CUBE C 175

## Order Code HT3711Z3

Zip HydroTap Design Range Chilled Filtered water appliance featuring a single under bench command centre including full colour interactive touch screen display with pin code protection, energy saving timer and 0.2 micron water filtration.

Manufacturing Code	0061AU0U0ZN1C
Capacity	Commercial
Disability Options	Unavailable
Boiling Cups per hour	n/a
Chilled Cups per hour	175



TapZip HydroTap Design Range CUBE Tap (Matte Black)Water PressureMin 172kPa - Max 700kPaWater Connection12.7mm BSPWater Supply RequirementsColdWater ValvesIntegrated 500kPa Pressure limiting valve and Dual Check ValvePower Rating0.3kW 220-240V 50/ 60HzBooster Power Ratingn/aPower Supply1 x 10Amp GPODimensionsH333mm x W280mm x D476mmProduct ApprovalsWaterMark, CE, RCM, ARCWarranty5 years (appliance warranty 36 months plus additional 24 months tank warranty)					
Water Connection  12.7mm BSP  Cold  Requirements  Water Valves  Integrated 500kPa Pressure limiting valve and Dual Check Valve  Power Rating  0.3kW 220-240V 50/ 60Hz  Booster Power Rating  n/a  Power Supply  1 x 10Amp GP0  Dimensions  H333mm x W280mm x D476mm  Product Approvals  Water Mark, CE, RCM, ARC	Тар	Zip HydroTap Design Range CUBE Tap (Matte Black)			
Water Supply Requirements  Water Valves  Integrated 500kPa Pressure limiting valve and Dual Check Valve  Power Rating  0.3kW 220-240V 50/ 60Hz  Booster Power Rating  n/a  Power Supply  1 x 10Amp GP0  Dimensions  H333mm x W280mm x D476mm  Product Approvals  WaterMark, CE, RCM, ARC	Water Pressure	Min 172kPa - Max 700kPa			
Requirements  Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve  Power Rating 0.3kW 220-240V 50/ 60Hz  Booster Power Rating n/a  Power Supply 1 x 10Amp GP0  Dimensions H333mm x W280mm x D476mm  Product Approvals WaterMark, CE, RCM, ARC	Water Connection	12.7mm BSP			
Power Rating 0.3kW 220-240V 50/ 60Hz  Booster Power Rating n/a  Power Supply 1 x 10Amp GP0  Dimensions H333mm x W280mm x D476mm  Product Approvals WaterMark, CE, RCM, ARC	• • •	Cold			
Booster Power Rating  n/a  Power Supply  1 x 10Amp GP0  Dimensions  H333mm x W280mm x D476mm  Product Approvals  WaterMark, CE, RCM, ARC	Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve			
Power Supply 1 x 10Amp GP0  Dimensions H333mm x W280mm x D476mm  Product Approvals WaterMark, CE, RCM, ARC	Power Rating	0.3kW 220-240V 50/ 60Hz			
Dimensions H333mm x W280mm x D476mm  Product Approvals WaterMark, CE, RCM, ARC	Booster Power Rating	n/a			
Product Approvals WaterMark, CE, RCM, ARC	Power Supply	1 x 10Amp GP0			
	Dimensions	H333mm x W280mm x D476mm			
Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)	Product Approvals	WaterMark, CE, RCM, ARC			
	Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)			

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

## Installation Detail

