



# ZIP HYDROTAP CELSIUS ALL-IN-ONE ARC BCSHA 100/75

Order Code MT1766Z11

Zip HydroTap Design Range CELSIUS All-In-One Boiling, Chilled & Sparkling Filtered water, plus Hot and Cold washing up water from a single tap. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, boiling water safety mode, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.

Manufacturing Code	2857AU0D4ZN1C
Capacity	Commercial
Disability Options	Unavailable
Boiling Cups per hour	100
Combined Chilled and Sparkling Cups per hour	75



<b>Water Pressure</b>	Min 250kPa - Max 700kPa
<b>Water Connection</b>	12.7mm BSP
<b>Water Supply Requirements</b>	Cold and Hot
<b>Water Valves</b>	Integrated 500kPa Pressure limiting valve and Dual Check Valve
<b>Power Rating</b>	2.125kW 220-240V 50/ 60Hz
<b>Booster Power Rating</b>	n/a
<b>Power Supply</b>	1 x 10Amp GPO
<b>Dimensions</b>	H333mm x W338mm x D461mm
<b>Product Approvals</b>	WaterMark, CE, RCM
<b>Wels Rating</b>	5 Star, 5.5 litres
<b>Warranty</b>	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)

Position the Tap such that it dispenses into the sink bowl with ample clearance for a cup or a tea pot

Ø50 Hole HydroTap® Celsius AIO Tap

Sink shown only

See Detail B

See Detail C

See Detail A

A. Kickboard Cut-Out

max. 43

B. Cabinet Floor Cut-Out

C. Cabinet Floor Cut-Out

Celsius Style All In One Tap

440

200 min.

333

Clearance Envelope

Ø140

CO<sub>2</sub> Cylinder

475

Connector with Strainer (Feeds Base Unit)

Melts cold water isolation valve (not supplied)

Hot water from domestic heater

Outlet Vent 240 - 230V, 50Hz GPO

100 min.

339

50 min.

50 min.

4 min. Buffer Pad Air Space

451

SECTION A-A

SCALE: 1:5

Celsius AIO Tap Profile

226

220

258

255

86

151

439.5

Ø52

Ø60

Zip Industries

Celsius AIO Tap 022 6000

www.zipindustries.com

022 6000 022 6000

Tap Detail



