



# ZIP HYDROTAP CELSIUS ALL-IN-ONE ARC BCHA 240/175

Order Code MT2714Z9

Zip HydroTap Design Range CELSIUS All-In-One Boiling & Chilled Filtered water, plus Hot and Cold washing up water from a single tap. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, boiling water safety mode, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.



Manufacturing Code	X
Capacity	Commercial
Disability Options	Unavailable
Boiling Cups per hour	240
Combined Chilled and Sparkling Cups per hour	175

<b>Water Pressure</b>	Min 172kPa - Max 700kPa
<b>Water Connection</b>	12.7mm BSP
<b>Water Supply Requirements</b>	Cold and Hot
<b>Water Valves</b>	Integrated 500kPa Pressure limiting valve and Dual Check Valve
<b>Power Rating</b>	2.1kW 220-240V 50/ 60Hz
<b>Booster Power Rating</b>	n/a
<b>Power Supply</b>	1 x 10Amp GPO
<b>Dimensions</b>	H333mm x W394mm x D464mm
<b>Product Approvals</b>	WaterMark, CE, RCM
<b>Wels Rating</b>	5 Star, 5.5 litres
<b>Warranty</b>	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)

Position the Tap such that it dispenses into the sink bowl with ample clearance for a cup or a tea pot

Ø50 Hole HydroTap® Celsius AIO Tap

Sink shown only

See Detail B

See Detail C

See Detail A

A. Kickboard Cut-Out

max. 43

B. Cabinet Floor Cut-Out

C. Cabinet Floor Cut-Out

Celsius Style All In One Tap

Booster

240 - 230V, 50Hz GPO

Clearance Envelope

IEC Connector

Inlet Vent

Outlet Vent

Connector with Strainer (Feeds Base Unit)

Main cold water isolation valve (not supplied)

Hot water from domestic heater

4 min. Buffer Pad Air Space

SECTION A-A

SCALE 1:5

Celsius AIO Tap Profile

Zip Industries

Celsius AIO Tap BT 240V/50

More info @ Zip Industries

0120 5944000

BT 240V/50

Tap Detail



