



# HYDROTAP G5 BC20 ARC BRUSHED ROSE GOLD



BOILING

CHILLED

FILTERED

## Order Code H52702Z05AU

Zip HydroTap Design Range Boiling, Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.



Manufacturing Code	H52702Z05AU
--------------------	-------------

Capacity	Commercial
----------	------------

Boiling Cups per hour	100
-----------------------	-----

Chilled Cups per hour	75
-----------------------	----

Tap	Zip HydroTap Design Range ARC Tap (Brushed Rose Gold)
-----	---

Water Pressure	Min 170kPa - Max 700kPa
----------------	-------------------------

Water Connection	1/2" BSP (G1/2)
------------------	-----------------

Water Supply Requirements	Cold
---------------------------	------

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
--------------	--

Power Rating	1.9kW 220-240V 50Hz
--------------	---------------------

Power Supply	1 x 10 Amp socket outlet
--------------	--------------------------

Dimensions	W280mm x D455mm x H333mm
------------	--------------------------

Product Approvals	WaterMark, RCM, ARC
-------------------	---------------------

Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)
----------	--

# Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)'

## Installation Detail

EKL2 HydroTap G5 v1.00 02.21 BC BC20

### Ventilation requirements

Contact your local service provider if ventilation is not suitable

#### Clearance envelope

Position the Tap and the Command Centre as close together as possible.

200  
333  
Command Centre width  
50

Air outlet louvre (if required)  
Cut-out in door/wall, towards the top of the cabinet

285  
60

Air inlet cut-out (required)  
Cut-out in cabinet floor

326  
19

### HydroTap Tap options

#### HydroTap Arc Tap

20  
40  
81  
175-225  
115  
162  
194  
303-353

#### HydroTap Cube Tap

20  
40  
81  
175-225  
115  
162  
194  
276-326

#### Standalone Font with Arc Tap

225  
223  
174  
162  
353  
40

#### Cutting detail

3 off.  $\varnothing$  10 holes @ 155mm PCD, equispaced  
174 for HydroTap Arc/Cube  
 $\varnothing$  140 hole for bowl  
 $\varnothing$  176 outline of Font  
 $\varnothing$  35 hole for tap

### Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).

$\varnothing$ 35mm hole for HydroTap Tap

200 min.  
333  
50 min.  
280  
50 min.  
455

HydroTap Arc  
Clearance Envelope  
Mains cold water isolation valve (not supplied)  
Air inlet grille  
IEC Flex & Plug 230-240V, 50Hz power outlet

4mm buffer pad air space

## HydroTap G5 BC Home, BC20

shown with HydroTap Arc

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

# Tap Detail



