



# HYDROTAP G5 BCHA40 4-IN-1 ARC TAP WITH ARC MIXER GUNMETAL



BOILING



CHILLED



HOT & AMBIENT

FILTERED

UNFILTERED

## Order Code H52822Z09AU

Zip HydroTap Design Range 4 in 1 Boiling, Chilled Filtered water plus Hot and Cold washing up water from two separate taps. This water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and a refillable CO2 cylinder. Easy to install integrated ventilation tray included.



Manufacturing Code	H52822Z09AU
Capacity	Commercial
Boiling Cups per hour	160
Chilled Cups per hour	125

Tap	Zip HydroTap Design Range ARC Tap (Gunmetal)
Water Pressure	Min 300kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.97kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet

Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)

## Installation Detail

BKL2 HydroTap G5 v1.00 02.21 BC40 BC60

### Ventilation requirements

Contact your local service provider if ventilation is not suitable.

**Clearance envelope**  
Position the Tap and the Command Centre as close together as possible.

**Vent tray (kit no. 93540)**

**Detail A. Air inlet grille**  
Cut-out in cabinet floor

**Detail B. Vent Tray air outlet**  
Cut-out in cabinet floor

**Tap Positioning**  
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).

### HydroTap Tap options

**HydroTap Arc Tap**

**HydroTap Cube Tap**

### Mixer Tap options

**Arc Mixer Tap**

**Cube Mixer Tap**

o35mm hole on sink or benchtop

**Vented mixer tap installation**  
Only cold water supply required

**HydroTap G5**  
**BC40 H, BC60 H, BC100 H**

shown with HydroTap Arc  
shown with Arc Mixer Tap (V)

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

