



HYDROTAP G5 BC40 ELITE BRUSHED ROSE GOLD



BOILING



CHILLED

FILTERED

Order Code H54703Z05AU

Zip HydroTap Design Range Boiling, Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.



Manufacturing Code	H54703Z05AU
--------------------	-------------

Capacity	Commercial
----------	------------

Boiling Cups per hour	160
-----------------------	-----

Chilled Cups per hour	125
-----------------------	-----

Tap	Zip HydroTap Design Range ELITE Tap (Brushed Rose Gold)
-----	---

Water Pressure	Min 170kPa - Max 700kPa
----------------	-------------------------

Water Connection	1/2" BSP (G1/2)
------------------	-----------------

Water Supply Requirements	Cold
---------------------------	------

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
--------------	--

Power Rating	1.97kW 220-240V 50Hz
--------------	----------------------

Power Supply	1 x 10 Amp socket outlet
--------------	--------------------------

Dimensions	W395mm x D464mm x H333mm
------------	--------------------------

Product Approvals	WaterMark, RCM, ARC
-------------------	---------------------

Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)
----------	--

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

BK1.2 HydroTap G5 v1.01 03.21 BC40 BC60

Ventilation requirements Contact your local service provider if ventilation is not suitable

HydroTap Tap options

Font options

Clearance envelope

Position the Tap and the Command Centre as close together as possible.

Vent tray (kit no. 93540)

Classic Plus

Classic

Elite Plus

Touch-Free Wave

100mm clearance envelope required.
For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

Raised Font with 135mm Extension part no. 95258

Font with 135mm Extension part no. 90915

Detail A. Air inlet grille Cut-out in cabinet floor

Detail B. Vent tray air outlet Cut-out in cabinet floor

Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

- 35mm hole for HydroTap

HydroTap G5
BC40, BC60, BC100

shown with "Classic Plus" Tap

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

