

HYDROTAP G5 B100 ELITE BRUSHED NICKEL



BOILING

FILTERED

Order Code H54707Z11AU

Zip HydroTap Design Range Boiling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.





Тар	Zip HydroTap Design Range ELITE Tap (Brushed Nickel)				
Water Pressure	Min 200kPa - Max 700kPa				
Water Connection	1/2" BSP (G1/2)				
Water Supply Requirements	Cold				
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve				
Power Rating	1.8kW 220-240V 50Hz				
Booster Power Rating	Zip HydroTap Booster 2.2kW 220-240V 50/60Hz				
Power Supply	2 x 10 Amp socket outlets				
Dimensions	W280mm x D313mm x H333mm				
Product Approvals	WaterMark, RCM				
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)				

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

Installation Detail

