



# HYDROTAP G5 BCHA40 4-IN-1 ELITE TAP WITH ARC MIXER MATTE BLACK



BOILING



CHILLED



HOT & AMBIENT

FILTERED

UNFILTERED

## Order Code H54822Z03AU

Zip HydroTap Design Range 4 in 1 Boiling, Chilled, Filtered water plus Hot and Cold washing up water from two separate taps. This water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders. Easy to install integrated ventilation tray included.



Manufacturing Code	H54822Z03AU
Capacity	Commercial
Boiling Cups per hour	160
Chilled Cups per hour	125

Tap	Zip HydroTap Design Range ELITE Tap (Matte Black)
Water Pressure	Min 300kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.97kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet

Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)

### Installation Detail

BKL2 HydroTap G5 v1.01 03.21 BC40 BC60

#### Ventilation requirements

Contact your local service provider if ventilation is not suitable

##### Clearance envelope

Position the Tap and the Command Centre as close together as possible.

##### Vent tray (kit no. 93540)

##### Detail A. Air inlet grille

Cut-out in cabinet floor

##### Detail B. Vent Tray air outlet

Cut-out in cabinet floor

#### HydroTap Tap options

##### Classic Plus

##### Classic

##### Elite Plus

##### Touch-Free Wave

100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

#### Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap      35mm hole for Mixer Tap

#### Mixer Tap options

##### Arc Mixer Tap

##### Cube Mixer Tap

##### Classic Mixer Tap

##### Accessible Mixer Tap

#### Vented mixer tap installation

Only cold water supply required

35mm hole in sink/benchtop for mixer tap

RED marked braided hose to HydroTap Command Centre MIXER OUT

BLUE marked braided hose to HydroTap Command Centre MIXER IN

WHITE marked braided hose

Braided hose to HydroTap Command Centre MAINS inlet

Mains water isolation valve (not supplied)

SCALE 1:5

ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

HydroTap G5  
BC40 H, BC60 H, BC100 H

shown with "Classic Plus" Tap  
and Arc Mixer Tap (V)

