



HYDROTAP G5 BCS20 CLASSIC PLUS MATTE BLACK



BOILING



CHILLED



SPARKLING

FILTERED

Order Code H55760Z03AU

Zip HydroTap Classic Plus Boiling, Chilled, Sparkling, Filtered water features simple, intuitive controls including continuous flow to fill bottles, Boiling water safety lock, and SteriTouch® antimicrobial protection impregnated within the new Classic Plus touch-pad for enhanced hygiene. The water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and a refillable CO2 cylinder. Easy to install integrated ventilation tray included.



Manufacturing Code	H55760Z03AU
--------------------	-------------

Capacity	Commercial
----------	------------

Boiling Cups per hour	100
-----------------------	-----

Combined Chilled and Sparkling Cups per hour	75
--	----

Tap	Zip HydroTap CLASSIC PLUS Tap (Matte Black)
-----	---

Water Pressure	Min 250kPa - Max 700kPa
----------------	-------------------------

Water Connection	1/2" BSP (G1/2)
------------------	-----------------

Water Supply Requirements	Cold
---------------------------	------

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
--------------	--

Power Rating	1.96kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W339mm x D460mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

Installation Detail

EKL2 HydroTap G5 v1.01 03.21 BCS BCS20

Ventilation requirements	HydroTap Tap options	Font options
<p>Clearance envelope Position the Tap and the Command Centre as close together as possible.</p>	<p>Classic Plus (116mm high, 216mm total height, 126mm depth, 46mm width) Classic (116mm high, 208mm total height, 126mm depth, 46mm width) Elite Plus (112mm high, 221mm total height, 134mm depth, 46mm width) Touch-Free Wave (116mm high, 214mm total height, 126mm depth, 46mm width, 100mm depth) 100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.</p>	<p>Raised Font with 135mm Extension (part no. 95258) (116mm high, 280mm total height, 116mm depth, 46mm width, 351mm total height) Font with 135mm Extension (part no. 90915) (116mm high, 280mm total height, 116mm depth, 46mm width, 351mm total height, 104mm depth, 219mm diameter)</p>
<p>Air outlet louvers (if required) Cut-out in door/wall, towards the top of the cabinet (285mm x 60mm)</p> <p>Air inlet cut-out (required) Cut-out in cabinet floor (max. 4mm x 326mm)</p>	<p>Tap Positioning Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory). 35mm hole for HydroTap Tap</p>	<p>Cutting detail Raised Font: 116mm diameter hole for bowl, 164mm diameter hole for tap, 10mm hole for M6 stud. Font: 108mm diameter hole for bowl, 104mm diameter hole for tap, 10mm hole for M6 stud.</p>
<p>4mm buffer pad air space</p>		
<p>Classic Plus Tap</p>		
<p>SCALE 1:5 ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.</p>		

**HydroTap G5
BCS20**

shown with "Classic Plus" Tap

