



HYDROTAP G5 BCHA60 4-IN-1 CLASSIC PLUS TAP WITH ARC MIXER MATTE BLACK



BOILING



CHILLED



HOT & AMBIENT

FILTERED

UNFILTERED



Order Code H55823Z03AU

Zip HydroTap Classic Plus 4 in 1 Boiling, Chilled, Filtered water plus Hot and Cold washing up water from two separate taps. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.

Manufacturing Code H55823Z03AU

Capacity Commercial

Boiling Cups per hour 160

Chilled Cups per hour 175

Tap Zip HydroTap CLASSIC PLUS Tap (Matte Black)

Water Pressure Min 300kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 2.1kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

Installation Detail

BKL2 HydroTap G5 v1.01 03.21 BC40 BC60

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

Vent tray (kit no. 93540)

HydroTap Tap options

100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

Mixer Tap options

Arc Mixer Tap

ø35mm hole on sink or benchtop

Cube Mixer Tap

ø35mm hole on sink or benchtop

Classic Mixer Tap

ø35mm hole on sink or benchtop

Accessible Mixer Tap

ø35mm hole on sink or benchtop

Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

ø35mm hole for HydroTap Tap ø35mm hole for Mixer Tap

Vented Arc Mixer Tap (optional)

4mm buffer pad air space

Clearance Envelope

Booster (BCS100 models)
Note: The 500mm braided hoses supplied cannot be lengthened

IEC Flex & Plug 230-240V, 50Hz power outlet

Air inlet

Vent tray
Note: should not be impeded by pipework

Mains cold water isolation valve (not supplied)

Tea piece

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

Vented mixer tap installation
Only cold water supply required

35mm hole in sink/benchtop for mixer tap

RED marked braided hose to HydroTap Command Centre MIXER OUT

BLUE marked braided hose to HydroTap Command Centre MIXER IN

WHITE marked braided hose

Braided hose to HydroTap Command Centre MAINS inlet

Mains water isolation valve (not supplied)

HydroTap G5

BC40 H, BC60 H, BC100 H

shown with "Classic Plus" Tap and Arc Mixer Tap (V)

