



# HYDROTAP G5 BCHA60 4-IN-1 CLASSIC PLUS TAP WITH ARC MIXER BRUSHED NICKEL



BOILING



CHILLED



HOT & AMBIENT

FILTERED

UNFILTERED



## Order Code H55823Z11AU

Zip HydroTap Classic Plus 4 in 1 Boiling, Chilled, Filtered water plus Hot and Cold washing up water from two separate taps. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.

Manufacturing Code H55823Z11AU

Capacity Commercial

Boiling Cups per hour 160

Chilled Cups per hour 175

Tap Zip HydroTap CLASSIC PLUS Tap (Brushed Nickel)

Water Pressure Min 300kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 2.1kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)'

## Installation Detail

BKL2 HydroTap G5 v1.01 03.21 BC40 BC60

**Ventilation requirements** Contact your local service provider if ventilation is not suitable

**Clearance envelope**  
Position the Tap and the Command Centre as close together as possible.

**Vent tray (kit no. 93540)**

**HydroTap Tap options**

**Tap Positioning**  
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap      35mm hole for Mixer Tap

**Mixer Tap options**

**Arc Mixer Tap**

**Cube Mixer Tap**

**Classic Mixer Tap**

**Accessible Mixer Tap**

**Vented mixer tap installation**  
Only cold water supply required

**Clearance envelope**

**Booster (BCS100 models)**  
Note: The 500mm braided hoses supplied cannot be lengthened

**IEC Flex & Plug 230-240V, 50Hz power outlet**

**Air inlet**

**Vent tray**  
Note: should not be impeded by pipework

**Mains cold water isolation valve (not supplied)**

**Tee piece**

**4mm buffer pad air space**

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

### HydroTap G5

#### BC40 H, BC60 H, BC100 H

shown with "Classic Plus" Tap and Arc Mixer Tap (V)

