



# HYDROTAP G5 BCSHA100 5-IN-1 CLASSIC PLUS TAP WITH ARC MIXER GUNMETAL



BOILING



CHILLED



SPARKLING



HOT & AMBIENT

FILTERED

UNFILTERED

## Order Code H55876Z09AU

Zip HydroTap Classic Plus 5 in 1 Boiling, Chilled, Sparkling, Filtered water plus Hot and Cold washing up water from two separate taps. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.



Manufacturing Code H55876Z09AU

Capacity Commercial

Boiling Cups per hour 240

Combined Chilled and Sparkling Cups per hour 175

Tap Zip HydroTap CLASSIC PLUS Tap (Gunmetal)

Water Pressure Min 300kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 2.15kW 220-240V 50Hz

<b>Booster Power Rating</b>	Zip HydroTap Booster 2.2kW 220-240V 50/60Hz
<b>Power Supply</b>	2 x 10 Amp socket outlets
<b>Dimensions</b>	W395mm x D464mm x H333mm
<b>Product Approvals</b>	WaterMark, RCM, ARC
<b>Wels Rating</b>	5 Star, 5.5 litres
<b>Warranty</b>	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)'

## Installation Detail

EKL2 HydroTap G5 v1 of 03.21 BCS60 BCS100

### Ventilation requirements

Contact your local service provider if ventilation is not suitable

#### Clearance envelope

Position the Tap and the Command Centre as close together as possible.

#### Vent tray (kit no. 93540)

#### Detail A. Air inlet grille

Cut-out in cabinet floor

#### Detail B. Vent Tray air outlet

Cut-out in cabinet floor

### HydroTap Tap options

#### Classic Plus

#### Classic

#### Elite Plus

#### Touch-Free Wave

100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

### Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

- 35mm hole for HydroTap Tap
- 35mm hole for Mixer Tap

### Mixer Tap options

#### Arc Mixer Tap

#### Cube Mixer Tap

#### Classic Mixer Tap

#### Accessible Mixer Tap

### Vented mixer tap installation

Only cold water supply required

- 35mm hole in sink/benchtop for mixer tap
- WHITE marked braided hose to HydroTap Command Centre MIXER OUT
- Braided hose to HydroTap Command Centre MAINS inlet
- RED marked braided hose to HydroTap Command Centre MIXER OUT
- BLUE marked braided hose to HydroTap Command Centre MIXER IN
- Mains water isolation valve (not supplied)

### Booster (BCS100 models)

Note: The 300mm braided hoses supplied cannot be lengthened

IEC Flex & Plug 230-240V, 10A, 50Hz power outlet

Air Inlet Note: should not be impeded by pipework

Vent tray Note: should not be impeded by pipework

Mains cold water isolation valve (not supplied)

## HydroTap G5

### BCS60 H, BCS100 H

shown with "Classic Plus" Tap and Arc Mixer Tap (V)

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

