



# HYDROTAP G5 BCHA40 4-IN-1 CLASSIC PLUS TAP WITH CUBE MIXER BRUSHED GOLD



BOILING



CHILLED



HOT & AMBIENT

FILTERED

UNFILTERED



## Order Code H55922Z07AU

Zip HydroTap Classic Plus 4 in 1 Boiling, Chilled, Filtered water plus Hot and Cold washing up water from two separate taps. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.

Manufacturing Code H55922Z07AU

Capacity Commercial

Boiling Cups per hour 160

Chilled Cups per hour 125

Tap Zip HydroTap CLASSIC PLUS Tap (Brushed Gold)

Water Pressure Min 300kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.97kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)'

## Installation Detail

BKL2 HydroTap G5 v1.01 03.21 BC40 BC60

**Ventilation requirements** Contact your local service provider if ventilation is not suitable

**Clearance envelope**  
Position the Tap and the Command Centre as close together as possible.

**Vent tray (kit no. 93540)**

**HydroTap Tap options**

100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

**Mixer Tap options**

**Arc Mixer Tap**

ø35mm hole on sink or benchtop

**Cube Mixer Tap**

ø35mm hole on sink or benchtop

**Classic Mixer Tap**

ø35mm hole on sink or benchtop

**Accessible Mixer Tap**

ø56mm hole on sink or benchtop

**Tap Positioning**

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

ø35mm hole for HydroTap Tap      ø35mm hole for Mixer Tap

**Vented Arc Mixer Tap (optional)**

4mm buffer pad air space

Clearance Envelope

Booster (BCS100 models)  
Note: The 500mm braided hoses supplied cannot be lengthened

IEC Flex & Plug 230-240V, 50Hz power outlet

Air inlet

Vent tray  
Note: should not be impeded by pipework

Tee piece

Mains cold water isolation valve (not supplied)

**Vented mixer tap installation**  
Only cold water supply required

**HydroTap G5**  
**BC40 H, BC60 H, BC100 H**

shown with "Classic Plus" Tap and Arc Mixer Tap (V)

