



HYDROTAP G5 CHA100 CELSIUS CUBE BRUSHED CHROME



CHILLED



HOT & AMBIENT

FILTERED

UNFILTERED

Order Code H59711Z01AU

Zip HydroTap Design Range CELSIUS Chilled Filtered water, plus Hot and Cold washing up water from a single tap. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.



Manufacturing Code H59711Z01AU

Capacity Commercial

Chilled Cups per hour 175

Tap Zip HydroTap Design Range CELSIUS CUBE Tap (Brushed Chrome)

Water Pressure Min 172kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold and Hot

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 0.34kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W280mm x D476mm x H333mm

Product Approvals WaterMark, RCM, ARC

Wels Rating

5 Star, 5.5 litres

Warranty

5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

EKL2 HydroTap G5 v1.00 02.21 C40 C100

<p>Ventilation requirements <small>Contact your local service provider if ventilation is not suitable</small></p> <p>Clearance envelope Position the Tap and the Command Centre as close together as possible.</p> <p>Vent tray (kit no. 93541)</p>		<p>HydroTap Tap options</p> <p>Celsius Arc Tap</p> <p>Celsius Cube Tap</p>	
<p>Detail A. Air inlet grille Cut-out in cabinet floor</p> <p>Detail B. Vent Tray air outlet Cut-out in cabinet floor</p> <p>Tap Positioning Position the Tap to dispense into the sink, allowing clearance for a cup or teapot.</p> <p>Ø35mm hole for Tap</p> <p>Mains hot water supply installation Hot and cold water supply required</p>		<p>IEC Flex & Plug 230-240V, 50Hz power outlet</p> <p>Air inlet grille</p> <p>Vent tray</p> <p>Note: should not be impeded by pipework</p>	
<p>SCALE 1:5 ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.</p>		<p>HydroTap G5 C40, C100 shown with Celsius Arc Tap</p>	

