



# HYDROTAP G5 BCHA100 CLASSIC ALL-IN-ONE BRUSHED CHROME



BOILING



CHILLED



HOT & AMBIENT

FILTERED

UNFILTERED



## Order Code H5A724Z01AU

Zip HydroTap Classic All-in-One Boiling, Chilled, Filtered water plus Hot and Cold washing up water from a single tap. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.

Manufacturing Code H5A724Z01AU

Capacity Commercial

Boiling Cups per hour 240

Chilled Cups per hour 175

Tap Zip CLASSIC All-in-One Tap (Brushed Chrome)

Water Pressure Min 300kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 2.1kW 220-240V 50Hz

Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/60Hz

Power Supply 2 x 10 Amp socket outlets

Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)

## Installation Detail

FKL2 HydroTap G5 v1.00 02.21 BC40 BC60

### Ventilation requirements

Contact your local service provider if ventilation is not suitable.

#### Clearance envelope

Position the Tap and the Command Centre as close together as possible.

#### Vent tray (kit no. 93540)

#### Detail A. Air inlet grille

Cut-out in cabinet floor

#### Detail B. Vent Tray air outlet

Cut-out in cabinet floor

#### Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot.

#### Classic Plus All-in-One Tap

### HydroTap Tap options

#### Classic Plus All-in-One Tap

#### Classic All-in-One Tap

#### Vented mixer tap installation

Only cold water supply required

## HydroTap G5

### BC40 H, BC60 H, BC100 H

shown with Classic Plus All-in-One Tap (Vented)

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

