



ZIP HYDROTAP B

Order Code HT1786Z1

Zip HydroTap Boiling, Filtered water appliance featuring a single under bench command centre including full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.

Manufacturing Code	1300AU0H2ZN1R
Capacity	Residential
Disability Options	Unavailable



Tap	Zip HydroTap CLASSIC Tap (Brushed Chrome)
------------	---

Water Pressure	Min 172kPa - Max 700kPa
-----------------------	-------------------------

Water Connection	12.7mm BSP
-------------------------	------------

Water Supply Requirements	Cold
----------------------------------	------

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
---------------------	--

Power Rating	1.425kW 220-240V 50/ 60 Hz
---------------------	----------------------------

Power Supply	1 x 10Amp GPO
---------------------	---------------

Dimensions	H333mm x W280mm x D313mm
-------------------	--------------------------

Product Approvals	WaterMark, CE, RCM
--------------------------	--------------------

Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)
-----------------	--

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.

- HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail



