

ZIP HYDROTAP C

Order Code HT1888Z3

Zip HydroTap Chilled, Filtered water appliance featuring a single under bench command centre including full colour interactive touch screen display with pin code protection and 0.2 micron water filtration.

Manufacturing Code	0015AU0H6ZN1R
Capacity	Residential
Disability Options	Unavailable



Тар	Zip HydroTap CLASSIC Tap (Matte Black)				
Water Pressure	Min 172kPa - Max 700kPa				
Water Connection	12.7mm BSP				
Water Supply Requirements	Cold				
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve				
Power Rating	0.125kW 220-240V 50Hz				
Power Supply	1 x 10Amp GP0				
Dimensions	H333mm x W280mm x D405mm				
Product Approvals	WaterMark, CE, RCM, ARC				
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)				

Installation Requirements

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.

- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

Installation Detail

