



ZIP HYDROTAP G4 5IN1 BCSHA 240/175 CUBE MIXER

Order Code HT1976Z3

Zip HydroTap 5in1 Boiling, Chilled, Sparkling, Filtered water plus Hot and Cold washing up water from two separate taps. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 3 energy saving modes including sensor activated "sleep when its dark", 0.2 micron water filtration and a refillable CO2 cylinder.

Manufacturing Code 5353AU0S0UN1C

Capacity Commercial

Disability Options Unavailable

Boiling Cups per hour 240

Combined Chilled and Sparkling Cups per hour 175



Tap Zip HydroTap CLASSIC Tap (Matte Black)

Water Pressure Min 250kPa - Max 700kPa

Water Connection 12.7mm BSP

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 2.3kW 220-240V 50/ 60Hz

Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz

Power Supply 2 x 10Amp GPO's (or 1 x 10Amp Double GPO)

Dimensions H333mm x W394mm x D464mm

Product Approvals WaterMark, CE, RCM, ARC

Wels Rating 5 Star, 5.5 litres

Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail



