

ZIP HYDROTAP ARC BA 240

Order Code HT2709Z6

Zip HydroTap Design Range Boiling, Ambient, Filtered water appliance featuring a single under bench command centre including full colour interactive touch screen display with pin code protection, boiling water safety mode, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.

Manufacturing Code	5101AU0T0ZN1C
Capacity	Commercial
Disability Options	Unavailable
Boiling Cups per hour	240



TapZip HydroTap Design Range ARC Tap (Gold)Water PressureMin 200kPa - Max 700kPaWater Connection12.7mm BSPWater Supply RequirementsColdWater ValvesIntegrated 500kPa Pressure limiting valve and Dual Check ValvePower Rating1.9kW 220-240V 50/ 60HzBooster Power RatingZip HydroTap Booster 2.2kW 220-240V 50/ 60HzPower Supply2 x 10Amp GPO's (or 1 x 10Amp Double GPO)DimensionsH333mm x W280mm x D313mmProduct ApprovalsWaterMark, CE, RCMWarranty5 years (appliance warranty 36 months plus additional 24 months tank warranty)						
Water Connection 12.7mm BSP Water Supply Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 1.9kW 220-240V 50/ 60Hz Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz Power Supply 2 x 10Amp GPO's (or 1 x 10Amp Double GPO) Dimensions H333mm x W280mm x D313mm Product Approvals WaterMark, CE, RCM	Тар	Zip HydroTap Design Range ARC Tap (Gold)				
Water Supply Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 1.9kW 220-240V 50/ 60Hz Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz Power Supply 2 x 10Amp GPO's (or 1 x 10Amp Double GPO) Dimensions H333mm x W280mm x D313mm Product Approvals WaterMark, CE, RCM	Water Pressure	Min 200kPa - Max 700kPa				
Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 1.9kW 220-240V 50/ 60Hz Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz Power Supply 2 x 10Amp GPO's (or 1 x 10Amp Double GPO) Dimensions H333mm x W280mm x D313mm Product Approvals WaterMark, CE, RCM	Water Connection	12.7mm BSP				
Power Rating 1.9kW 220-240V 50/ 60Hz Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz Power Supply 2 x 10Amp GPO's (or 1 x 10Amp Double GPO) Dimensions H333mm x W280mm x D313mm Product Approvals WaterMark, CE, RCM	• • •	Cold				
Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz Power Supply 2 x 10Amp GPO's (or 1 x 10Amp Double GPO) Dimensions H333mm x W280mm x D313mm Product Approvals WaterMark, CE, RCM	Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve				
Power Supply 2 x 10Amp GPO's (or 1 x 10Amp Double GPO) Dimensions H333mm x W280mm x D313mm Product Approvals WaterMark, CE, RCM	Power Rating	1.9kW 220-240V 50/ 60Hz				
Dimensions H333mm x W280mm x D313mm Product Approvals WaterMark, CE, RCM	Booster Power Rating	Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz				
Product Approvals WaterMark, CE, RCM	Power Supply	2 x 10Amp GPO's (or 1 x 10Amp Double GPO)				
	Dimensions	H333mm x W280mm x D313mm				
Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)	Product Approvals	WaterMark, CE, RCM				
	Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)				

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

Installation Detail

