



ZIP HYDROTAP ELITE 4IN1 BCHA 160/125 ARC MIXER

Order Code HT4222

Zip HydroTap Design Range 4 in 1 Boiling, Chilled, Filtered drinking water plus Hot and Cold washing up water from two separate taps. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, boiling water safety mode, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.

Manufacturing Code 5260AU0E0AN1C

Capacity Commercial

Disability Options Unavailable

Boiling Cups per hour 160

Chilled Cups per hour 125



Tap Zip HydroTap Design Range ELITE Tap

Water Pressure Min 250kPa - Max 700kPa

Water Connection 12.7mm BSP

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 2.1kW 220-240V 50/ 60Hz

Booster Power Rating n/a

Power Supply 1 x 10Amp GPO

Dimensions H333mm x W394mm x D464mm

Product Approvals WaterMark, CE, RCM, ARC

Wels Rating 5 Star, 5.5 litres

Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail



