

ZIP HYDROTAP ELITE 5IN1 BCSHA 160/175 CUBE MIXER

Order Code HT4375Z8

Zip HydroTap Design Range 5 in 1 Boiling, Chilled, Sparkling, Filtered water plus Hot and Cold washing up water from two seperate taps. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 2 energy saving modes, 0.2 micron water filtration and a refillable CO2 cylinder.

Manufacturing Code	5253AU0E4UN1C
Capacity	Commercial
Disability Options	Unavailable
Boiling Cups per hour	160
Combined Chilled and Sparkling Cups per hour	175



Тар	Zip HydroTap Design Range ELITE Tap			
Water Pressure	Min 250kPa - Max 700kPa			
Water Connection	12.7mm BSP			
Water Supply Requirements	Cold			
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve			
Power Rating	2.3kW 220-240V 50/ 60Hz			
Booster Power Rating	n/a			
Power Supply	1 x 10Amp GPO			
Dimensions	H333mm x W394mm x D464mm			
Product Approvals	WaterMark, CE, RCM, ARC			
Wels Rating	5 Star, 5.5 litres			
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)			

Installation Requirements

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

Installation Detail

