



ZIP HYDROTAP ELITE C 175

Order Code HT4711Z5

Zip HydroTap Design Range Chilled Filtered water appliance featuring a single under bench command centre including full colour interactive touch screen display with pin code protection, energy saving timer and 0.2 micron water filtration.

Manufacturing Code	0061AU0E3ZN1C
Capacity	Commercial
Disability Options	Unavailable
Boiling Cups per hour	n/a
Chilled Cups per hour	175



Tap	Zip HydroTap Design Range ELITE Tap (Brushed Rose Gold)
Water Pressure	Min 172kPa - Max 700kPa
Water Connection	12.7mm BSP
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	0.3kW 220-240V 50/ 60Hz
Booster Power Rating	n/a
Power Supply	1 x 10Amp GPO
Dimensions	H333mm x W280mm x D476mm
Product Approvals	WaterMark, CE, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

Installation Detail



