



# ZIP HYDROTAP CELSIUS ARC CS175

Order Code MT2762Z11

Zip HydroTap Design Range CELSIUS Chilled and Sparkling Filtered water, plus Hot and Cold washing up water from a single tap. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, 0.2 micron water filtration and a refillable CO2 cylinder.

|  |               |
|--|---------------|
| Manufacturing Code                           | 0053AU0C4ZN1C |
| Capacity                                     | Commercial    |
| Disability Options                           | Unavailable   |
| Combined Chilled and Sparkling Cups per hour | 175           |



|                                  |  |
|----------------------------------|--|
| <b>Tap</b>                       | Zip HydroTap Design Range Celcius ARC Tap (Brushed Nickel)                     |
| <b>Water Pressure</b>            | Min 250kPa - Max 700kPa  |
| <b>Water Connection</b>          | 12.7mm BSP   |
| <b>Water Supply Requirements</b> | Cold and Hot   |
| <b>Water Valves</b>              | Integrated 500kPa Pressure limiting valve and Dual Check Valve                 |
| <b>Power Rating</b>              | 0.45kW 220-240V 50/ 60Hz   |
| <b>Booster Power Rating</b>      | n/a  |
| <b>Power Supply</b>              | 1 x 10Amp GPO  |
| <b>Dimensions</b>                | H333mm x W280mm x D476mm   |
| <b>Product Approvals</b>         | WaterMark, CE, RCM, ARC  |
| <b>Wels Rating</b>               | 5 Star, 5.5 litres   |
| <b>Warranty</b>                  | 5 years (appliance warranty 36 months plus additional 24 months tank warranty) |

# Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)

## Installation Detail



