

Zip Hydroboil Plus



It's water. Refreshed.

Instant on-wall boiling water

The recently redesigned Zip Hydroboil Plus range, delivers boiling water instantly from a reliable, wall-mounted unit. As well as saving time, the Hydroboil Plus saves businesses energy and money too. Costing little to run, energy efficient design and electronic controls minimise power consumption, while simple-to-use fingertip control brings you a cup-full or teapot-full of boiling water at a time.

With all the benefits of the Hydroboil, the Hydroboil Plus also features energy-saving Power-Pulse™ technology, inactivity and low light sleep modes and is equipped with a two-way safety tap and safety lock.



New Product code	Old Product code	Tank size (litres)	*Cups at one time	Heat up time (Inlet 15°C)	Heat up time (Inlet 10°C)	Rated voltage and power	Dimensions (mm) W x D x H	Filled weight (Kg)
303562	HP003	3.0	18	16mins	17mins	220-240V, 50Hz, 1500W	289 x 180 x 431	12.5
305562	HP005	5.0	30	16mins	17mins	220-240V, 50Hz, 2400W	318 x 198 x 465	16.5
307562	HS007	7.5	45	23mins	24mins	220-240V, 50Hz, 2400W	318 x 198 x 578	20.5

*Standard cup size 167ml

FEATURES & BENEFITS

DELIVERY RATE

Up to 240 cups at a time.

RECOVERY RATE

Up to 360 cups/hour.

INSTANT

Boiling water instantly for tea, coffee, cooking.

OPERATION

Designed to operate within 1°C of boiling point.

TECHNOLOGY

Patented Twin chamber, Steam-Heat-Boost technology.

TANK

Crevice free, stainless steel boiling tank, with top and bottom access ports.

TAP

Unique two-way cool touch tap with safety lock.

CASE

White enamelled steel case.

ELEMENT

Long life incolloy sheathed, embedded rod type element.

SLEEP MODES

Inactivity and low light.

TIMER

Integral 24/7 timer.

SPECIFICATION TYPE

Instant boiling water heater	Twin chamber
Stainless steel boiling chamber	Service access ports top & bottom
Control	Electronic
Element	Incoloy sheathed embedded rod
Thermostat	Capillary type

CAPACITY

Capacity	Model range 3L, 5L, 7.5L
----------	--------------------------

ELECTRICAL

Voltage supply	220 - 240V AC 50Hz
Power supply	1 x 13 amp double pole isolation switch or socket outlet
Installation	Must comply with current IEE regulations

PLUMBING

Wholesome cold water inlet supply required	Yes
Supply pressure range	0.07 MPa (0.7 bar) - 0.5 (5 bar)
Inlet pipe	15mm connections
Vent pipe	15mm connections
Vent discharge	Visible tundish or drainage board
Installation	Must comply with current water supply regulations

WARRANTY

2 years on-site parts and labour on site	Terms and conditions apply (see supplied manual)
--	--

HYDROCARE PACKAGES AVAILABLE

Commercial - Yearly Plan	Full breakdown cover including parts and labour
	Comprehensive preventative maintenance cover

ACCESSORIES

ZD200 Drip Tray	340mm x 190mm x 20mm, 19.5mm drainage access.
FL064 Inline filter	For scale, taste & odour, up to 7.5Litre models
FL104 Inline filter	For scale, taste & odour, above 7.5Litre models
ZE001 Cup dispenser	Stainless steel
ZE002 Cup dispenser	White plastic

All dimensions in mm

